

CROWN[®]

Jewel OF COOKING

**Two-Sided Grills made
Easier, Faster, Smarter ...
all at the touch of a button.**

**Available in
Electric or Gas**

Easier

Modular; customize the cook surface size & number of upper platens
Requires a smaller footprint than flat grill cooking
Totally automatic; reduces labor requirements
Reduces product waste

Faster

Cooks both sides of the product simultaneously
Cooks the product 2/3 faster than traditional flat grills
Cooking speed eliminates the need to hold product before serving

Smarter

Solid state controls are intuitive and easy to operate
Customizable to personalize to your menu
Expandable to grow with your future offers
Self diagnostic to easily correct problems

Safer

Provides consistent temperatures across the entire cook surface
Automatically applies the exact pressure to the product to assure consistent product temperatures

Specification sheets can be found @ taylor-company.com



TAYLOR

United Technologies

Rockton, IL
taylor-company.com
815.624.8333

A worldwide leader
in foodservice
equipment innovation



Model L810 Shown



Model # Model Description	Model L810	Model L812	Model L820	Model L822	Model L828	Model L811	Model L813	Model L819	Model L821
Lower Cooking Surface Heat Source	Electric	Electric	Electric	Electric	Electric	Gas	Gas	Gas	Gas
Upper Platen Heat Source	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Cooking Surface Dimensions	36"	36"	24"	24"	12"	36"	36"	24"	24"
Installation	Floor Model	Floor Model	Floor Model	Floor Model	Floor Model	Floor Model	Floor Model	Floor Model	Floor Model
Upper Platens	3	2	2	1	1	3	2	2	1
Cooking Zones	3	3	2	2	1	3	3	2	2
Programmable Controls	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Gapping	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Grease Collection	External Side	External Side	External Side	External Side	External Side	External Side	External Side	External Side	External Side
Dimensions w/d/h (in/mm)	40-5/16" (w) 1024mm (w) 38-13/16" (d) 986mm (d) Adjustable (h)	40-5/16" (w) 1024mm (w) 38-13/16" (d) 986mm (d) Adjustable (h)	28-3/16" (w) 716mm (w) 38-13/16" (d) 986mm (d) Adjustable (h)	28-3/16" (w) 716mm (w) 38-13/16" (d) 986mm (d) Adjustable (h)	15" (w) 381mm (w) 38-13/16" (d) 986mm (d) Adjustable (h)	40-5/16" (w) 1024mm (w) 40-13/16" (d) 1037mm (d) Adjustable (h)	40-5/16" (w) 1024mm (w) 40-13/16" (d) 1037mm (d) Adjustable (h)	28-3/16" (w) 716mm (w) 40-13/16" (d) 1037mm (d) Adjustable (h)	28-3/16" (w) 716mm (w) 40-13/16" (d) 1037mm (d) Adjustable (h)